

CMKREC024 RF314-TC

Temperature Data Logger with Probe



The Diligence™ WiFi RF314-TC data logger measures and records temperature via a range of Comark thermocouple probes.

The probe can be used in a wide range of temperature situations such as measuring core food temperatures during cooking and in hot holding cabinets or wells.

Comark offers two options for managing the data collected with Diligence WiFi data loggers:

- Diligence WiFi software for set up, data logging and data review on a local PC. Set up features include data logger name, choice of °F or °C scale, sample rate and high/low alarms.
- Comark Cloud has the same features as Diligence WiFi software and in addition offers unlimited storage of your temperature and humidity records. Data can be viewed for multiple locations from anywhere in the world using any internet enabled device.

The collected temperature data is transmitted via your WiFi network and when configured, the data logger can be placed anywhere within range of the WiFi network. Alarm notifications sent in real time by email and text message.

If connectivity is temporarily lost, the data logger will continue to log readings until it can communicate again with Diligence WiFi software or Comark Cloud. The range of the data logger can be extended using WiFi extenders.

The Diligence WiFi RF314-TC data logger is a low powered battery device. Battery charge is typically > 6 months depending on transmission rate. The battery can be recharged via a PC or by mains power using the RF320/US power supply unit, which is available as an accessory.

Features

- Measurement range -454°F to +2372°F (probe dependent)
- Rechargeable internal lithium polymer battery
- Easy data logger set-up using free PC software application
- Temperature data logger with K type thermocouple probe
- Supports J, K, N, T type probes
- Temperature selection in °F or °C
- Data can be viewed via the graphing tool or can be exported to MS Excel
- Configurable high and low alarms with indicator
- Alarm delay prevents false alarms due to defrost cycles or operational conditions
- Wireless connectivity to PC via WiFi
- Max and Min readings
- IEEE 802.11b/g/n compliant
- Protection rating IP55
- Memory stores all data even if WiFi is temporarily disconnected
- Fully featured LCD segment display
- Low battery indicator
- WiFi connection indicator
- USB port used for recharging (can only be recharged when the unit is between +32 to +104°F)
- Supplied with Wall Bracket and Micro USB lead

Comark Cloud

Comark Cloud service makes your data universally accessible from any internet enabled device. Manage your devices and make changes to any data logger settings remotely, including changing alarm levels. With the Cloud service you can:

- Store data on-line
- Monitor multiple sites
- View on mobile devices
- Have multiple users
- Receive email alerts when alarms occur or if a device needs attention

Comark RF314-TC

Temperature Data Logger with Probe



Specifications

Battery Life	3-12 months depending on frequency of transmissions
USB supply voltage	5V (typical)
Temperature measurement range (probe dependent)	-454°F to +2372°F
Operating temperature range	-4°F to +140°F
Logging rate (user configurable)	Transmission rate from every 10 seconds to 12 hours
Transmission period (user configurable)	1 minute to 12 hours
Temperature measurement resolution	0.1°F
Temperature display resolution	0.1°
Temperature accuracy (probe dependent)	±1.8°F
Supplied probe temperature Accuracy	±1.8°F
Supplied probe temperature range	+32°F to +482°F
Supplied probe length	6"
Logger dimension	Height 3 1/4" x Width 3 3/4" x Depth 7/8"
WiFi Compliance	IEEE 802.11b/g/n compliant, supports WEP, WPA/WPA2 encryption and enterprise networks (MS-CHAPv2, PEAP, EAP-FAST, EAP-TTLS)

For more details for the Diligence WiFi range, please see www.comarkusa.com.com

Diligence WiFi

